Temperature and Humidity Sensor – outdoor

Product ref.: 150573A0 (white) | 150574A0 (anthracite)





Supply voltage	2x 1.5 V LR6/Mignon/AA		
Current consumption	30 mA max.		
Battery life	5 years (typ.)		
Degree of protection	IP44		
Ambient temperature	-20 to +55 °C		
Temperature measuring range	-20 to +55 °C		
Measuring range humidity	0 to 99 %		
Dimensions (W x H x D)	59 x 82 x 41 mm		
Weight	100 g (including batteries)		
Radio frequency band	868.0-868.6 MHz 869.4-869.65 MHz		
Typ. open area RF range	220 m		
Accuracy humidity (typically)	±3 % (in a range between 20 to 80 %)		
Accuracy temperature (typically)	± 0.3 °C (in a range between 5 to 60 °C)		











Product features

- Measures the temperature and humidity in outdoor areas
- Collected weather data is displayed via the Homematic IP app
- Various applications in connection with other Homematic IP devices (e.g. for ventilation or de-humidification control)
- Immediately ready for use thanks to battery operation and radio communication
- Flexible and easy installation on the wall thanks to the supplied plugs and screws or use as standing unit
- Available in white (HmIP-STHO) and anthracite (HmIP-STHO-A).
- To enable operation, the device has to be connected with one of the following solutions:
 - Homematic IP Access Point with free smartphone app and free cloud service
 - Central Control Unit CCU2/CCU3 with local user interface WebUI
 - Third-party solutions of partners

Logistical data

Version	White	Anthracite
Product reference	150573A0	150574A0
EAN code	4047976505739	4047976505746
Short description	HmIP-STHO	HmIP-STHO-A
Packing unit	90	90
Packing dimensions	122 x 112 x 48 mm	122 x 112 x 48 mm
Weight incl. packaging	179.8 g	179.8 g

Package contents

Homematic IP Temperature and Humidity Sensor – outdoor	
Screws (2x) and plugs (2x)	
1.5 V LR6/Mignon/AA batteries (2x)	
User manual	

Homematic IP is a brand of eQ-3 AG Subject to modifications. www.homematic-ip.com Version 1.4